

Widen your horizons in labelling.



SG112-ex

Print large format labels at top speed

Applications



Manufacturing



Transport & Logistics



Automotive



Chemical



Powered **On Site** /

satoeurope.com

SG112-ex Technical Specification*

PRINTING SPECIFICATION			SG112-ex
Printing Method			Thermal Transfer and Direct Thermal.
Resolution			12 dots/mm (305 dpi).
Print Mode	Standard Model		Continuous, Tear-off.
	Cutter Model		Continuous, Tear-off, Cutter, Cut & Print.
Max. Print Area	Width / Length, mm (inch)		266.7 mm (10.5") / 420 mm (16.5").
Media Aligment			Centered.
Print Speed			75, 100, 125, 150 mm/sec (3, 4, 5).
CONSUMABLES SPECIFICATION (Recommended to use printer supplies manufactured or certified by SATO)			
Media Sensor type			I-Mark Sensor (Reflective) / Label Gap Sensor (Transmissive).
Media Thickness (Label + Liner)			80 - 270µm (0.08 - 0.27mm) *Use media 120µm (0.12mm) or greater in thickness for Auto Feed mode *Use media 210µm (0.21mm) or lesser in thickness for Cutter option
Media Type			Roll or fan-fold die cut labels.
Roll Shape			Diameter maximum 200mm (8") on 76mm (3") internal core.
Label Wind Direction			Face-in / Face-out.
Ribbon	Width		145 ~ 273mm (5.7" to 10.7").
	Length / Diameter		300m (984.25ft.) maximum / Ø 70.0mm maximum.
	Core Diameter		Inside Diameter : Ø 25.6mm.
	Wind Direction		Face-in.
Label Size	Continuous	Width	128 ~ 297 mm (including liner 131 ~ 300 mm) / 5.0" ~ 11.7" (including liner 5.2" ~ 11.8").
		Length	30 ~ 420 mm (including liner 33 ~ 423 mm) / 1.2" ~ 16.5" (including liner 1.2" ~16.6").
	Tear Off	Width	128 ~ 297 mm (including liner 131 ~ 300 mm) / 5.0" ~ 11.7" (including liner 5.2" ~ 11.8").
		Length	40 ~ 420 mm (including liner 43 ~ 423 mm) / 1.6" ~ 16.5" (including liner 1.7" ~ 16.7").
	Tray (Cutter Model Only)	Width	128 ~ 297 mm (including liner 131 ~ 300 mm) / 5.0" ~ 11.7" (including liner 5.2" ~ 11.8").
		Length	40 ~ 117 mm (including liner 43 ~ 120 mm) / 1.6" ~ 4.6" (including liner 1.7" ~ 4.7").
	Cutter (Cutter Model Only)	Width	128 ~ 297 mm (including liner 131 ~ 300 mm) / 5.0" ~ 11.7" (including liner 5.2" ~ 11.8").
		Length	40 ~ 420 mm (including liner 43 ~ 423 mm) / 1.6" ~ 16.5" (including liner 1.7" ~ 16.7").
SYMBOLOGIES			
Linear Barcode			UPC-A, UPC-E, JAN/EAN, CODE39, CODE93, CODE128, GS1-128(UCC/EAN128), ISBT128, CODABAR(NW-7), ITF, Industrial 2of5, Matrix 2of5, MSI, POSTNET, BOOKLAND, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, GS1 DataBar Expanded Stacked , Intelligent Mail Barcode (IMb). *GS1 DataBar was formerly called RSS.
2D Code			QR Code (including Micro QR) PDF417 (including MicroPDF) MAXI Code(Ver.3.0) GS1 DataMatrix(ECC200 Ver.2.0).
ELECTRICAL SPECIFICATION (Interface Characteristics)			
Interfaces	USB (Type A & B)	2.0 High Speed *Type A implemented in front of printer.	
	LAN	10BASE-T/100BASE-TX auto-switching Protocol TCP/IP : LPR, FTP, TELNET, SNMP, SNTP, IPv4 / IPv6.	
	RS-232C	DSUB 9 pin.	
	IEEE1284	Amphenol 36 pin.	
	EXT	Amphenol 14 pin dedicated connector.	
	SD Card Slot	1 slot.	
On-Board Memory	USB Type A	2.0 High Speed type A connector.	
	(Flash ROM):	Standard Memory Size 40 MB User area 4.5 MB.	
	(SDRAM):	Standard Memory Size 64MB.	
CPU Type		32bit RISC-CPU 250MHz.	
LCD Specifications		Graphic LCD (Horizontal 128 dots x Vertical 64 dots) with backlight (White/Orange switchable), Displayed languages: English, Simplified Chinese, Japanese.	
LED Specifications		POWER(Green/Orange), ONLINE(Green), STATUS(Green/Red), LABEL(Red), RIBBON(Red).	
OPERATING CHARACTERISTICS			
Power Supply	Input Voltage / Frequency	AC100 V ~ 240 V ±10% (full range) / at 50/60 Hz.	
Size		W475mm x D313.4mm x H319.2mm (H515.5 mm with cover open). 164mm: Media exit area. 85.1mm: Tray (Cutter Model Only).	
Weight	Standard Model	Approx. 20.0Kg / 44.1 lbs. (Media/Ribbon excluded).	
	Cutter Model	Approx. 23.1Kg / 51 lbs. (Media/Ribbon excluded).	
Temperature	Operating Environment	5 ~ 40°C (Non-condensing).	
	Storage Environment	-5 ~ 60°C (Non-condensing).	
Humidity	Operating Environment	30 ~ 80% RH (Non-condensing).	
	Storage Environment	30 ~ 90% RH (Non-condensing).	
MISCELLANEOUS			
Operation Buttons			LINE, FEED, FUNCTION, ENTER, CANCEL Arrow buttons.
Print Setting Tool			SATO-All-In-One-Tool.
Standards & Agency Approvals			FCC Part 15 Subpart B Class A/ICES-003 Class A, CE(EN55032, EN55024), CCC(GB/T9254-2008, GB17625.1-2012) BSMI(CNS13438), UL 60950-1/CSA C22.2 No.60950-1, CE, Nemko-GS EN60950-1, CCC(GB4943.1-2011), BSMI(CNS14336-1), BIS(IS 13252).
Self-diagnostic Function			Head breakage check, Label end detection, Ribbon end detection, Ribbon near end detection (Less than 15m), Cutter error (when cutter unit is installed).
OPTIONS			
Accessories			RTC (Calendar) kitm Simple stacker (ST-10PI US) External feed module (UW-10PI US)

*Available in standard model and cutter model



Contact Xact: Xact, 20-24 Gibraltar Row, King Edward Industrial Estate,
Liverpool, L3 7HJ T: 0151 479 3020 E: info@xactpack.co.uk
xactpack.co.uk



© 2020 SATO CORPORATION. All rights reserved.
For more information, please contact your local
SATO office, or visit: satoeurope.com